



PS-1511

Product Description:

P-THERM® PS-1511 is a hyper-soft silicone based thermally conductive gap filler with an embedded fiberglass support and 125 micron removable polyester carrier.

Construction / Properties:

Property	Value	Test Method
Color	Gray	Visual
Carrier Type	Polyester Film	--
Carrier Thickness	125 micron	--
Thickness Range	0.5mm - 5.0mm	ASTM D374
Thermal Conductivity	1.0 W/m K	ASTM D5470
Dielectric Breakdown Strength	>5 kV _{AC}	ASTM D149
Hardness (Shore 00)	<5	ASTM D2240
Continuous Use Conditions	-60 - 200 C	QSP-754
Flammability Rating	V-0	UL 94

Features:

- Good Thermal Conductivity
- Excellent Compression Characteristics
- Excellent Wet-Out
- Superb Flexibility
- Excellent Converting Properties
- RoHS and HF Compliant

Hyper-Soft Silicone
with Embedded
Fiberglass Support
Polyester Carrier



Specific tests should be performed by the end user to determine the product stability for the particular application.

For Additional Information:

E-mail: sales@polymerscience.com
Toll Free: +1 888.533.7004
Web: www.polymerscience.com
Revision: 032519



www.marianinc.com
1-800-773-0062

